



# Einhell

## BG-DW 1300 N Deep Well Pump

Art.-No. 41.709.42

The robust deep well pump is most suitable for delivery of clear water from reservoir, well and shafts. The deep well pump is also able to pump the water up from large depths and because of the multi-stage rotor-system the water can be transfer with much pressure. The integrated motor-thermo protection protects the pump against overloading. The pump is equipped with an external switching box and a 22 meter long connecting cable. The vertical pressure line connection with an integrated return valve consists of brass and has a 1 1/2" female thread.

### Features

- Robust pressure connection with brass insert and an integrated return valve
- Pump housing consist of rust-free stainless steel (1)
- Stainless steel dirt trap (2)
- External switching box (3)
- Overload switch (4)
- On-/Off switch (5)
- Operation display (6)
- Mains display (7)
- 20 m drain cord (8)

### Technical data

- Mains: 230 V ~ 50 Hz
- Power: 1,300 W
- Delivery quantity max.: 5,000 l/h
- Delivery height max.: 65 m
- Immersion depth max.: 20 m
- Water temperature max.: 35 °C
- Hose connection: 1 1/2" female thread
- Contaminant: clear water
- Mains cable: 2 m
- Connecting cable: 22 m
- Pump-Ø: 102 mm (suitable for KG-pipe DN 100)
- Plastic pump wheels: 10 pcs
- Net weight: 15.7 kg
- Gross weight: 17.85 kg
- Packing dimensions: 913 x 207 x 203 mm
- Bar code: 4006825 549348
- Sales unit: 1 pc

### Performance data:

