

KYOWA

Manufacturer of Test Pumps & High-Pressure
Washing Machines — Offers

TEST PUMP

HYDRAULIC PRESSURE TEST PUMP

*Epoch-making Mechanism
Featuring Rational &
Functional Merits..... Developed Under Kyowa's
Power Test Pump Technology!!*



Utility model & design
registration being applied for.

[HAND OPERATED] Model T-50K-P/T-100K

■ SPECIFICATIONS (50kg/cm² pressure gauge is available if desired.)

Item Model	Maximum Pressure	Plunger Diameter	Stroke	Rate of Water Suction Per Stroke	Capacity of Water Tank	Size of Discharge Port	Weight	Dimensions L×H×W	Accessories
T-50K-P	50kg/cm ²	22mm	35mm	13cc.	4.5ℓ Plastic tank	1/4	3.3kg	320×300 ×200mm	Pressure gauge 1/4PT 1 Pressure hose 1 Union joint 1/2 1 Bushing 1/2×1/4 1
T-100K	100kg/cm ²	22mm	35mm	13cc.	5.2ℓ Steel tank	1/4	7.0kg	370×300 ×210mm	Pressure gauge 1/4PT 1 Ultra high pressure hose 1/4 PF×1m 1 1/4 nipple 1

*Specifications may be subject to change without notice. *KYOWA's products are patented. Give careful attention to imitations.

■ FEATURES OF KYOWA TESTER

1. High-precision stainless steel (SUS 304) ball valve is applied as the valve.
2. Valve seat is replaceable with ease.
3. Water tank of rust-free plastic (P.P.) construction assures unchanging cleanliness.
(Models T-50K and T-100K are of vinyl-coated steel sheet construction.)
4. The plunger packing used is standard product, O-ring No. P-22 which is available in local hardware dealers.
5. All fulcrum pins applied are made of stainless steel.
6. A full range of accessories are provided to permit on-the-spot job
7. Matchless compact and light-weight design in the world.

 **KYOWA CO., LTD.**