

XINYUE Brick Sawing Machine PRC



ZJ350

Feature:

- 1 Cutting head supported by bearings allows the head to be positioned at any cutting depth with high efficiency
- 2 Water hose connection is available as standard parts
- 3 Handle grips offer comfortable operation
- 4 Dual belt drive ensures reliable power transmission
- 5 Wheel for easy moving to different working site

| Type | ZJ350 |
|---------------------|----------------------|
| Power supply | 400V, 3 phase, 50Hz |
| Motor | 2.2 kw |
| Blade Dimension | 350 mm |
| Max. Cutting Depth | 125 mm |
| Max. Cutting Length | 450 mm |
| Table Travel | 515 mm |
| External Dimension | 1200 x 656 x 1330 mm |
| Net Weight | 78 kg |




QB350



| Type | QB350-6 | QB350-8 | QB350-10 | QB350-12 | QB350-15 |
|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| Power supply | 400V, 3 phase, 50Hz | 400V, 3 phase, 50Hz | 400V, 3 phase, 50Hz | 400V, 3 phase, 50Hz | 400V, 3 phase, 50Hz |
| Motor | 3 kw | 3 kw | 3 kw | 3 kw | 3 kw |
| Blade Dimension | 350 mm | 350 mm | 350 mm | 350 mm | 350 mm |
| Max. Cutting Height | 40 mm | 40 mm | 40 mm | 40 mm | 40 mm |
| Max. Cutting Length | 600 mm | 800 mm | 1000 mm | 1200 mm | 1500 mm |
| Cutting Angle | 0° - 45° | 0° - 45° | 0° - 45° | 0° - 45° | 0° - 45° |
| Speed | 2800 rpm | 2800 rpm | 2800 rpm | 2800 rpm | 2800 rpm |
| Weight | 77 kg | 108 kg | 120 kg | 130 kg | 145 kg |

XINYUE Brick Cutting Machine PRC



ZQ150



ZQ330 & ZQ430G



ZQ430P-A



ZQ530L & ZQ650L

| Model | ZQ150 | ZQ330 | ZQ430G | ZQ430P-A | ZQ530L | ZQ650L |
|-------------------|------------------------|--------------------|--|-----------------------------------|----------------------------------|----------------------------------|
| Cutting range | Length 150 mm | Length 330 mm | Length 430 mm | Length 430 mm | Length 530 mm | Length 650 mm |
| | Height 40 - 90 mm | Height 10 - 120 mm | Height 10 - 300 mm | Height 40 - 155 mm | Height 10 - 120 mm | Height 10 - 120 mm |
| Blade | Fixed, 4 cutting edges | | | | | |
| Spindle | 1 spindle | 2 spindles | 2 spindles | 1 spindle | 2 spindles | 2 spindles |
| Supporting plates | Fixed | Springs | | | | Fixed |
| Handle | | | Optional lengthening bar, 600 mm | Optional lengthening bar, 1200 mm | Optional lengthening bar, 600 mm | Optional lengthening bar, 850 mm |
| Application | Paving stones | Paving stones | Sand-lime bricks, slabs, thick blocks, kerbstones. | Paving stones | Paving stones, large slabs | Paving stones, large slabs |
| Weight | 13 kg | 13 kg | 54 kg | 59.5 kg | 58 kg | 76 kg |
| Size | 640 x 350 x 410 mm | 640 x 350 x 410 mm | 1030 x 285 x 630 mm | 1250 x 285 x 650 mm | 990 x 285 x 435 mm | 1160 x 320 x 540 mm |



| Type | HS-75D | HS-100D |
|-----------------|---|---|
| Power supply | 400V, 3 phase | 400V, 3 phase |
| Motor | 3.3 KW | 3.3 KW |
| Two speeds | 22.5 m/s | 22.5 m/s |
| | 45 m/s | 45 m/s |
| Working height | Adjustable, 620-1280 mm | Adjustable, 620-1280 mm |
| Belt size | 75 x 2000 mm | 100 x 2000 mm |
| Dust extraction | Additional, Standard dust extraction connections on the machine | Additional, Standard dust extraction connections on the machine |
| Weight | 93 kg | 108 kg |



| Type | PN100 |
|---------------------|---|
| Power supply | 400V, 3 phase |
| Belt | 100 x 2000 mm |
| Roller dimensions | 1/2" – 2 1/2" |
| Motor | 3 KW |
| Two speeds | 1400 rpm (Stainless Steel) |
| | 2800 rpm |
| Grinding options | 1. Pipe notcher |
| | 2. Deburring table on the top |
| | 3. Belt sander |
| Angles Pipe notcher | 30° - 90°(0° - 60°) |
| Dust extraction | Additional, Standard dust extraction connections on the machine |